

## 3893-00

### Stainless steel eyewash, freeze resistant

Krusman eye/facewash for outside use with stainless steel pipes and green/white stripe. Self-draining eye/facewash with built-in flow control and filter for each individual spray head. Stay-open ball valve, operated by a pull handle. Designed for a minimum flow of 28 l/min at 2.4 bar pressure. Freeze resistant and manufactured for Ex-classified environments. The model is available for Ex-classified or non Ex-classified environments.

Emergency signs are enclosed with each eyewash.

#### TECHNICAL DATA

The shower is constructed for outdoor installation. It is insulated and heat traced in order to prevent freezing. The material is approved for installation in hazard environments.

**Water pressure:** Automatic function for pressure between 2.4-6.5 bar with built-in flow controls and filters. If the water pressure exceeds 6.5 bar a pressure reducing valve must be installed.

**Material:** Valves and pull handle are manufactured in stainless steel. Stainless steel pipes and fittings. The spray heads are manufactured in polypropylene plastic.

**Trace heated:** Self-regulating heating-cable, 4 m (10W/m).

**Insulation:** Waterbased foam insulation.

**Surface:** Black PEH plastic pipes. Meet DIN and ISO standards.

**Water supply standard:** 1" male.

**Options:** Flange connection, alarm, strobe light, foot pedal, thermostat heating cable.

#### TECHNICAL INFORMATION

Flow rate: 28 L/min                      Width: 350 mm

Water supply: 1" male                      Height: 1100 mm

Depth: 650 mm

