

## Model 6005

### Insulated booth with safety station

Emergency booth 6005 has insulated walls, ceiling and floor made of 40 mm insulated panels with finishes of painted sheet steel. The booth has inner floor with plastic carpet and floor drain without water trap. The booth has mounted fluorescent (strip) lighting in the ceiling. The lighting is suitable for sanitary areas.

Safety station 3874, inside the booth is manufactured in galvanized pipes and a shower head in stainless steel. Including ball valve, with non-returning spring, operated by a pull handle and a pull rod for a crawling person. The emergency shower is designed for a minimum flow of 76 l/min at 2.4 bar pressure. The eyewash 3864, has individual spray heads with built-in flow control and filter. The eyewash is designed for a minimum flow of 28 l/min at 2.4 bar pressure. The flow and pressure regulator of the eyewash work automatically at 2,4 - 6,5 bar. If the pressure exceeds 6,5 bar it will be necessary to install a reducing valve.

The unit is mobile with a fork-lift truck. Emergency signs are enclosed with each emergency shower booth. This product is manufactured in accordance to ANSI Norm Z358.1-2004 and SS-EN 15154-1 & 2:2006.

#### TECHNICAL INFORMATION

Flow rate body: 76 L/min	Width:	1175mm
Flow rate eyes: 28 L/min	Height:	2700 mm
Water supply: 3/4" female	Depth:	1300 mm

