

## 7040

### Semi portable tank shower 1350L

Combined emergency shower and eyewash with 1350 liter tank, internal pump and heating for year-round use. The emergency shower is equipped with an internal pump and heating element. The tank is made of stainless steel. The shower can be moved with a forklift and its 1350 liter tank is sufficient for a 15-minute emergency shower with a flow of 76 L/min (emergency shower) and 14 L/min (eyewash).

The integrated switches in the combination shower valves control the pump located inside the tank. The combination shower is emptied when the pump is turned off, so that no water remains in the shower. With the treatment agent, the water remains usable for 6 months.

The flushing time is 15 minutes. Material: Tank SS304, emergency shower SS316. Available complete in SS316 on request. Power: 230VAC 1 Ph 50-60 Hz.

Emergency signs are enclosed with each safety station.

The model is also available for EX-classified environments. Version with heating cable and insulated combination shower is also available. Please contact our sales office for more information.

#### TECHNICAL INFORMATION

Flow rate (body):	ca 76 L/min	Width:	1500 mm
Flow rate (eye):	ca 14 L/min	Height:	2390 mm with attached shower
Water supply:	1" (DN25)	Depth:	1800 mm



Manufactured in accordance to ANSI Norm Z358.1- latest edition and EN 15154- latest edition.